

Emergency Aid Camp Infrastructure



Hiremax 6500HMSLR Long Running Portable Petrol Generator



- Honda four stroke engine
- Noise compliant using the latest low noise engine
- Dual voltage output c/w overload protection
- Fully welded wrap around frames for maximum protection
- Heavy duty smooth waveform brushless maintenance free alternator
- Twin engine and alternator mounts



Generator Specification

Frequency	50Hz
Phase	Single
Voltage	230 / 115
Power	6.5 kVA 5.2 kW
Acoustic pressure level Lw(a)	97
Noise level dB(a) @7m	72

Control Box & Sockets

BS 4343 Sockets	1 x 115v 16A 1 x 115v 32A 1 x 230v 16A 1 x 230v 32A
Voltage selector switch	YES
Protection	Push button MCB

Engine Specification

Engine	Honda GX390
Distribution	O.H.V
Start	Recoil
Fuel	Unleaded Petrol
Autonomy (h) @75% load	6.2
Consumption (l/h) @ 75% load	2.5
Tank (l) metal	15.5
Oil alert / Low oil shutdown	YES
Capacity cm ³	389
Oil capacity (litres)	1.1

Alternator Specification

Manufacturer	NSM
Model	M100SG
Type	Heavy duty brushless Maintenance free
Regulation	Mechanical
Protection class	IP23
Insulation class	H

Options

Single voltage
Electric start
AVR (Automatic Voltage Regulator)
3 Phase

Dimensions

Length (mm)	710
Width (mm)	510
Height (mm)	600
Weight (kg)	76



Butyl Products Ltd.

Lingfield House, 11 Radford Crescent, Billericay, Essex,
CM12 0DW, United Kingdom. T: +44 (0) 1277 653 281
F: +44 (0) 1277 657 921 E: enquiries@butylproducts.co.uk
W: butylproducts.co.uk