Emergency Aid Camp Infrastructure

Pelican 351

3" x 3" Self Priming Diaphragm Sludge Pump With Lombardini 15LD225 Diesel Engine

Applications include:

Mud, Sludge, Sewage pumping (and other thick liquids that flow)



- Cast aluminium for portability and durability
- Thermoplastic rubber diaphragm and polyurethane flap valves
- Solids handling to 40mm Ø
- Continuous dry running without damage
- Self priming to 7.5m
- Screwed BSP Male connections
- Easy cleanout & maintenance Mounted on 2 wheel site trolley




Special Feature:


Base of pump can be rotated through 90° for access through doors and narrow spaces etc.

Powered by a Lombardini lightweight industrial air cooled single cylinder diesel engine, model 15LD225 developing 2.7kW at a nominal 2,750rpm, complete with recoil start, (optional E.12volt electric start), 3 litre 4 hour fuel tank, silencer, throttle, dry type air, oil and fuel filters. Set is supplied with pump and engine operating and instruction manuals

Standard Options:

- A. Individual plywood case packing.
- B. Pump spares for 1000 hours normal operation.
- C. Engine spares for 1000 hours normal operation.
- D. Hose kit
- E. Electric start
- F. Suction lance for pit latrines
- G. Quick couplings







Butyl Products Ltd.

Lingfield House, 11 Radford Crescent, Billericay, Essex, CM12 0DW, United Kingdom. T: +44 (0) 1277 653 281 F: +44 (0) 1277 657 921 E: enquiries@butylproducts.co.uk

W: butylproducts.co.uk

